



Flange Data : PER ANSI B16.24

150 LB CLASS

	<u>INLET</u>	<u>SUCTION & DISCH.</u>
ID	1½"	2"
OD	5"	6"
B.C.	3⅞"	4¾"
# Holes	4	4
Hole Ø	⅝"	¾"

General Operating Conditions

- Motive Pressure Up to 175 PSI
- Motive Flow Up to 225 GPM
- Suction Lift Up to -23 Feet
- Discharge Head Up to 80 Feet
- Suction Capacity Up to 155 GPM



926-2" Bill of Materials

Part #	Part Name	Qty	Material
92-6-A	Body	1	BRONZE ASTM B62
92-6-B	Diffuser	1	BRONZE ASTM B62
92-6-C	Nozzle	1	MONEL
92-6-D	Bolts	6	316 Stainless Steel
92-6-E	Nut	6	316 Stainless Steel
92-6-F	Lockwasher	6	316 Stainless Steel
92-6-G	Gasket	1	Garlock Gylon 3510

UNLESS OTHERWISE SPECIFIED 1. REMOVE ALL BURRS, BREAK ALL OUTSIDE CORNERS EDGES .005 TO .010 X 45 DEG. CHAMFER 2. STANDARD TOLERANCE .XX = ± .01 .XX C = ± .06 .XXX = ± .005 .XXXX = ± .0005 FRACTIONS = ± .01 CONCENTRICITY = ± .005 ANGULAR = ± .5 DEG MATERIAL : <p style="text-align: center;">BRONZE</p>	926-2" Bilge & Ballast Stripping Eductor 1½" x 2" x 2"		VITA-MOTIVATOR CO., INC. TEANECK, N.J.
	CHKD BY	DATE	PART NO.
	APPD BY	DATE	DRAWING NO. [- 926-2 1/2] REV C
SCALE HALF	SHEET 1 OF 2		