VM TYGER-ATX-2½" Multi-Jet Eductor Kit

The VM TYGER-ATX Portable Multi-Jet is used on board tankers, oil rigs and vessels of all types. The eductor is fitted with a multi-jet nozzle, which provides a straight through unrestricted suction path for superior no clog flow of liquid and solid mixtures. The TYGER ATX is excellent for cleaning sludge, muck, sand, grain, cement and coal.

The <u>TYGER-ATX Eductor</u> is used to remove slurries from tanks, sumps, pits, cargo and ballast spaces. This small and lightweight ejector allows access to inaccessible spaces for removal of many solids and liquid mixtures.

TYGER-ATX Portable Eductor Kit – includes: And a "Tyger" in your Tarke VM # 92N-2½"L Bronze or Aluminum Eductor with Monel Nozzle 1 pc INLET HOSE - Fire "Motive Pressure" Hose, 75' (23M) x 1 pc **DISCHARGE** 11/2" with brass (NPT) couplings for eductor inlet 21/2" SUCTION HOSE - Non-Collapsible PVC Full Vac. Hose, 20' (6 M) 1 pc x 1½" with brass coupling for eductor suction **DISCHARGE HOSE - PVC (or) Heavy Duty EPDM Rubber Water** 1 pc Discharge Hose 75' (23 M) x 21/2" with Brass coupling to eductor discharge. 1 ea. **Suction Check Valve Spare Nozzle** 1 ea. 1 ea. On - Off Ball Valve for shut off В Ε SUGGESTED USES Keeping tank bottoms dry during tank or hold Α washing operations Will handle slurries and solids in suspension INLET Pumping water out of holds during firefighting operations Regular or emergency pumping of liquids from ballast, bilge or cargo spaces Powered by water pressure or the same liquid as suction fluid This model can be lowered directly into the В liquid to be suctioned.

ח

Flow Data	Suction Capac Up to 154 GPI Up to 35 M3/I	M	Suction Lift Up to -20 Feet Up to -6 Meters	Up	narge Hea to 80 Feet 25 Meter		Motive Press 50 -150 PS 3 – 10 Bar	T	150 – 2	<u>e Flow</u> 25 GPM 1 M3/H
Materials of Construction BODY & Diffuser Nozzle Throat Wear Lining			Standard Eductor Aluminum Monel 316 Stainless Steel			Optional Materials Bronze 316 Stainless Steel, Monel				
<u>Dimensions</u>	<u>Inlet</u>	1½"	(40)	<u>A</u>	<u>B</u>	<u>C</u>	<u>D</u>	<u>E</u>	Ţ	<u>WT</u>
	<u>Suction</u>	2 ½"	(65)	21"	61/4"	143/4"	31/4"	7 ³/₄"	11/2"	20 #
	<u>Discharge</u>	2 ½"	(65)	533	159	374	82	197	38	9 kg

SUCTION

Up to 20' of suction hose can be attached.